

### Password is "Four S"

- 1 "S"trong body
- 2 "S"imple operation
- 3 "S"mart design
- 4 "S"mooth performance



#### Kit Configuration

- 100mm Ball Pan & Tilt Fluidhead
- + Single Telescopic Pan Bar
- + 100mm Bowl Two Stage Aluminum Tripod
- + Floor Spreader

#### Specifications

##### SP 100

Payload	Max. 15kg / 33lbs
Optimum Load	8 - 13kg / 17.6 - 28.6lbs
Max Height	1668mm / 65.6"
Min Height	580mm / 22.8"
Transport Length	869mm / 34.2"
System Weight	7.7kg / 16.9lbs
Tilt Range	+70° / -90°
Counterbalance	Fixed
Pan & Tilt Drag	2 Steps
Camera Plate	Sliding Plate with 3/8" screws ( 2pcs)
Sliding Range	+25mm / -53mm +0.9" / -2.0"

# SP100



SP 100 head front side



SP 100 head back side

SHOTOKU Corp  
6-10-10 Futago, Takatsu-ku,  
Kawasaki, Kanagawa  
213-0002, Japan  
TEL: +81(0)44-833-3356  
FAX: +81(0)44-812-0932  
Email: info@shotoku.co.jp

SHOTOKU Ltd  
Unit 1, 96-104 Church Street,  
Staines, Middlesex,  
TW18 4YA, U.K.  
TEL: +44(0)1784-224650  
FAX: +44(0)1784-224659  
Email: info@shotoku.co.uk

SHOTOKU Inc  
438 Amapola Avenue  
Suite 125 Torrance,  
CA 90501 U.S.A  
TEL: +1 310-782-8491  
FAX: +1 310-782-8963  
Email: info@shotoku.tv